Product datasheet

OSRAM BATTERYcharge 5PIN | 1PHASE | 32 AMP

Charging Cable for electric and plug-in hybrid vehicles



Type 2 to Type 1 Charge at home and on the moveType 2 to Type 15PIN | **1PHASE**



32 Ampere Connects to any charging unit or station with a 32A (1 Phase) type 2 connection



7.2 kWh Charge your 60kW battery in ca. 8 hours



5m cable length Ergonomic handles for optimal handling and a cable length of 5 meters

Drive with OSRAM into a more emission-free future



Discover the world of electric driving with OSRAM. Charge your all-electric or plug-in hybrid vehicle type 1 at any 32 A charging station (1 phase) equipped with a type 2 plug. The charging cable is equipped with ergonomic handles for optimal handling and has a cable length of 5 meters. It is suitable for use at public charging stations and at home. In addition, the charging cables are equipped with dust protection caps and tested for waterproofness according to IP65 and shock resistance according to IK10. Even when connected, the electrical contact points are protected against the ingress of dust and splash water in accordance with IP65 and IK10. The scope of delivery also includes a durable, compact storage bag to neatly store the cable after charging. In addition, the product is TÜV and CE certified and comes with a 2-year guarantee*

Product datasheet

Technical data


Product information

Order reference	OCC13205
Storage Case	Yes
Number Of Phases	1
Vehicle Charger Type	Туре1
Charging Point Charger Type	Туре2

Electrical data

Nominal wattage	7200 W
Nominal voltage	240 V
Nominal current	32 A

Dimensions & weight



Length	5000 mm
Width	55.0 mm
Height	130.0 mm
Lifespan	
Guarantee	2 years
Additional product data	
Operating Temperature	-40 +80 °C
Certificates & standards	
Standards	TÜV/CE
Type of protection	IP65
IK Class	IK10

Product datasheet

Country specific categorizations

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	04-10-2022	
Primary Article Identifier	4052899624146	
Declaration No. in SCIP database	In work	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899624146	BATTERY charge 5PIN 1PHASE 32 AMP	Sleeves 1	340 mm x 200 mm x 108 mm	7.34 dm³	2820.00 g
4052899624214	BATTERY charge 5PIN 1PHASE 32 AMP	Shipping carton box 4	496 mm x 406 mm x 387 mm	77.93 dm ³	12230.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

